North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

[] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

[X] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

[X] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

[] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Flecto Co.

Product Name: Elite Diamond Finish Semigloss (DISCONTINUED)



MATERIAL SAFETY DATA SHEET

HMIS CODES: H PRODUCT NAME: ELITE DIAMOND FINISH SEMIGLOSS

PRODUCT CODE: 2001

SERESEESESSES SECTION | - MANUFACTURER IDENTIFICATION

94608

MANUFACTURER'S NAME: FLECTO CO. ADDRESS: 1000 45th Street, Oakland, CA EMERGENCY PHONE: 1 800 255 3924 INFORMATION PHONE: 1 800 635 3286 DATE REVISED : 04-10-92 NAME OF PREPARER : Edward M. Quesada

REASON REVISED : Update

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ======== -----

HAZARDOUS COMPONENTS		OSHA PEL	ONAL EXPOSURE LIMITS ACGINITLY OTHER	VAPOR PRESSURE mm Hg 0 TEMP	WEIGHT PERCENT
1-METHYL-2-PYRROLIDINONE PROPYLENE GLYCOL DIPROPYLENE GLYCOL MONGMETHYL ETHER n-BUTOXYPROPANOL	872-50-4	100 PPM	100 PPM	0.3 68F	(5.0%
	57-55-6	NGT EST.	NOT EST.	0.2 68F	(5.0%
	34590-94-9	100 PPM	100 PPH	0.6 77F	(5.0%
	5131-66-8	NOT EST.	NOT EST.	0.6 68F	(5.0%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title 411 and of 40 CFR 372 are present. ***

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

SPECIFIC GRAVITY (H20=1): 1.0 EVAPORATION RATE: SLOWER THAN ETHER BOILING RANGE: 338 to 370 Deg F VAPOR DENSITY: HEAVIER THAN AIR COATING V.O.C. : 2.61 LB/GL (

COATING V.O.C.: 2.61 LB/GL (313 G/L)
MATERIAL V.O.C.: 1.07 LB/GL (129 G/L)
SOLUBILITY IN WATER: Complete
APPEARANCE AND ODOR: Milky appearance with a slight acrylic odor.

METHOD USED: SETA FLASH POINT: NONE

1.1% UPPER: 14.4% FLAMMABLE LIMITS IN AIR BY VOLUME-LOWER:

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
Material will not support combustion. Use water to keep fire exposed containers coci to reduce pressure.

UNUSUAL FIRE AND EXPLOSION HAZARDS Keep away from heat.



2001

MATERIAL SAFETY DATA SHEET

PAGE 2 OF 3

STABILITY: STABLE CONDITIONS TO AVOID

Excessive heat, corrosive atmospheres, excessive Eging.

INCOMPATIBILITY (MATERIALS TO AVOID) May react with strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS Not applicable.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

BERRESESSESSESSESSES SECTION VI - HEALTH HAZARD DATA SESSESSESSESSESSES

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE May cause irritiation to mose, throat or lungs.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE May cause irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE May be harmful if swallowed.

HEALTH HAZARDS (ACUTE AND CHRONIC)
The health effects of this product have not been tested.

CARCINOGENICITY: NTP? NO LARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush immediately with copicus quantities of running water for at least 15 minutes. Consult physician.
Skin Contact: Wash affected areas with soap and water.
Inhaled: Remove to fresh air, restore breathing, consult physician.
Swallowed: Call physician immediately.



MATERIAL SAFETY DATA SHEET

PAGE 3 OF 3

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Avoid breaching vapors. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Normal waste disposal methods. Do not incinerate in closed containers.

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store or use near heat. Do not get in eyes.

OTHER PRECAUTIONS

OD NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

PIRATORY PROTECTION

Approved mask or respirator for organic vapors as necessary.

VENTILATION

Adequate volume and pattern to avoid vapor concentration in excess of TLV or LEL.

PROTECTIVE GLOVES

Protective gloves required for direct contact.

EYE PROTECTION

Safety goggles or safety plasses with shields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear protective clotning whenever possible.

WORK/HYGIENIC PRACTICES

Do not take internally.

DISCLAIMER

THIT INFORMATION IS FURNISHED WITHOUT WARRANTY. REPRESENTATION, OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE UT OF THE FLECTO COMPANY'S KNOWLEDGE OR CETAINED FROM SCURCES BELIEVED TO BE ACCURATE. THE FLECTO COL SHALL HAVE NO LEGAL RESPONSIBILITY FOR ANY INFORMATION PROVIDED HERE. READ PRODUCT LABEL.